

iDock



iRoom's iDock Basic is the perfect solution for secure storage of your iPad™.

The iDock Basic is integrated into the wall.

A special flush-mounted socket is used for this purpose. The iDock Basic is then connected via PoE, USB, 12V oder 230 V power supply and inserted into the flush-mounted socket. Done! Now you can place your iPad™ into the docking station; the rechargeable iPad™ battery is automatically charged. Naturally you can also use the iPad™ while it is in the iDock Basic.

TouchCode Version is a secure solution to protect your iPad™ while it is docked.



TouchCode Keypad



iDock Landscape with Alu Faceplate

Features

- Turns an iPad® into an In-Wall panel
- Proximity sensor controls the opening mechanism
- potential-free contact (e.g. switch) for securing the iDock using a keyswitch
- vertical and horizontal format
- iDock also allows table top application
- iDock available in black and white
- Faceplates available in pianoblack, opal white, silver and brushed aluminium
- Quality: 200.000 times tested opening mechanism
- At a power outage the iDock Basic opens automatically and releases the iPad™
- crush protection feature (opens when resistance at closing)
- DIP switch for configuration (e.g. enable/disable iPad internal speakers etc.)
- TouchCode (secure release) and Manual versions (not motorized, no Audio, no DIP Switch) available

Specifications

Dimensions iDock Portrait (WxHxD)	220,0 x 310,0 x 66,8 mm
Dimensions flush-mountet socket Portrait (WxHxD)	214,1 x 304,2 x 70,0 mm
Dimensions cut-out for flush-mounted socket (WxHxD)	205,0 x 295,0 x 65,0 mm
Dimensions iDock Landscape (WxHxD)	351,9 x 226,4 x 68,2 mm
Dimensions flush-mountet socket Landscape (WxHxD)	305,0 x 214,1 x 65,0 mm
Dimensions cut-out for flush-mounted socket (WxHxD)	295,0 x 205,0 x 65,0 mm
Voltage supply (depending on version)	PoE, USB, 12 V DC or 85 – 264 V AC
Outputs	Stereo Audio / RCA (not Manual version)
Weight	1.700 g
Operating conditions	0°C – 35°C
	20%-95% RH non-condensing
Touch Sensor	Capacitive proximity sensor
External contact	potential-free contact (deactivated on delivery)
Secure-open function	in case of power outage
Installation position	Vertical – max. tilting angle: approx. 3° in all directions
Scope of delivery	iDock Basic: white or black; vertical or horizontal format
	Faceplate: piano black, opal white
	Installation material, Operating instructions
Accessories	flush-mounted socket 53BB-B

Designs

Designs and CAT No's	iDock vertical black	iDock vertical white	iDock horizontal black	iDock horizontal white
Faceplate Pianoblack	53HSS	53HWW + iDBL-HS2	53QSS	53QWW + iDBL-QS2
Faceplate opal white	53HSS + iDBL-HW2	53HWW	53QSS + iDBL-QW2	53QWW
Faceplate silver	53HSS + iDBL-HG2	53HWW + iDBL-HG2	53QSS + iDBL-QG2	53QWW + iDBL-QG2
Faceplate brushed Aluminium	53HSS + iDBL-HA2	53HWW + iDBL-HA2	53QSS + iDBL-QA2	53QWW + iDBL-QA2

iDock is available in vertical and horizontal format, in black and white. The faceplates are available in Pianoblack, Opal white, silver and brushed Aluminium.

